

# CITOFLEX R26

## Cored Wires High-strength steels

Citoflex R26 is a rutile flux cored wire suitable for welding high strength fine-grain structural steels. Low spatter with easy slag removal and regular bead appearance.

Classification	
AWS	A5.29: E 101 T1-G M H4
EN	12535: T 62 5 Mn2,5Ni P 1 H5

Approvals	Grades
ABS	
DNV	
LRS	

see Appendix, Classification Society Approvals, for details pag. 521

### Analysis of all-weld metal (Typical values in %)

C	Mn	Si	P	S	Cr	Ni	Mo	Nb	V	N	Cu
0.08	1.35	0.35	≤ 0.015	≤ 0.015	-	2.20	-	-	-	-	-

### All-weld metal Mechanical Properties

Heat Treatment	Yield Strength N/mm <sup>2</sup>	Tensile Strength N/mm <sup>2</sup>	Elongation A5 (%)	Impact Energy ISO - V (J) -50°C	Hardness
As Welded	≥ 620	700-890	≥ 18	≥ 47	-

Gas test: Acc. To EN 439: M21(Arcal 21)

**Shielding Gas:** Acc. To EN 439: M21(Arcal 21-Atal 6)

### Materials

S(P)460-S(P)620

### Storage

Keep dry and avoid condensation

### Current condition and welding position

DC+



**Packaging data:** K300 kg, 16

Diameters	1,2					
-----------	-----	--	--	--	--	--